



All Purpose Replacement Drivelines



21HP @ 540 RPM or 31HP @ 1000 RPM PTO Shaft (uni size 23.80mm x 61mm)

T20 L=1010mm Yoke 1 3/8x6 SPL BE

T20 L=1510mm Yoke 1 3/8x6 SPL BE

35HP @ 540 RPM or 55HP @ 1000 RPM PTO Shaft (uni size 27mm x 74.60mm)

T40 L=1010mm Yoke 1 3/8x6 SPL BE

T40 L=1010mm Yoke 1 3/8x6 SPL & 2 Plate Friction Clutch F12

T40 L=1510mm Yoke 1 3/8x6 SPL BE

64HP @ 540 RPM or 100HP @ 1000 RPM PTO Shaft (uni size 30.20mm x 92mm)

T60 L=1010mm Yoke 1 3/8x6 SPL BE

T60 L=1010mm Yoke 1 3/8x6 SPL & 2 Plate Friction Clutch F22

T60 L=1510mm Yoke 1 3/8x6 SPL BE

*An alternative to end yokes, a range of clutches are available to suit.
Walterscheid can change end yokes to suit (charges will apply)*

1300 WALTER

www.walterscheid.com.au



All Purpose Replacement Drivelines

95HP @ 540 RPM or 139HP @ 1000 RPM PTO Shaft (uni size 34.93mm x 106.30mm)

T80 L=1010mm Yoke 1 3/8x6 SPL BE

T80 L=1010mm Yoke 1 3/8x6 SPL & 4 Plate Friction Clutch F42

T80 L=1510mm Yoke 1 3/8x6 SPL BE

110HP @ 540 RPM or 150HP @ 1000 RPM PTO Shaft (uni size 36mm x 89mm)



AGC2500 L = 1010mm Yoke 1 3/8x6 SPL BE

AGC2500 L = 1510mm Yoke 1 3/8x6 SPL BE

120HP @ 540 RPM or 166HP @ 1000 RPM PTO Shaft (uni size 42mm x 104mm)



AGC2600 L = 1010mm Yoke 1 3/8x6 SPL BE

AGC2600 L = 1410mm Yoke 1 3/8x6 SPL BE



Reduce HP ratings by 40% for severe conditions

*An alternative to end yokes, a range of clutches are available to suit.
Walterscheid can change end yokes to suit (charges will apply)*

Locations Australia Wide

Adelaide • Brisbane • Bunbury • Hobart • Mackay

Melbourne • Newcastle • Perth • Townsville • Illawarra

1300 WALTER

www.walterscheid.com.au