

WELD ON BALL ENDS

CAT	Dimension							Part Number	Installing Walterscheid Ball End Stick Weld (using Walterscheid Electrodes Part. 094008) or gas shielded arc welding only. An anhydrogenous high-strength, deep penetration weld is required.
	Ø D	A	L	H	R	B	C		
1	22.1	35	60	70	35	18	-	307547	
2H	28.4	45	75	90	42.5	22	-	306832	
3/2	28.1	45	80	100	50	25	-	307342	
3/2H	28.4	45	80	100	50	25	-	306382	
3H	37	45	80	100	50	25	-	306332	
3	32	51	80	100	50	25	-	308187	
2	26.2	35	70	70	42.5	22	-	307196	
2H	28.4	35	70	70	42.5	22	-	306383	
3	37	47.5	80	100	50	25	32	308762	
3	37	45	80	90	50	25	20	200438	
1/2	28.7	30.73	100.3	-	38	17.6	-	200911	
3	37	45	80	100	50	25	37	201505	
3	29	45	80	100	50	25	37	201506	
3/2	28	45	80	90	50	25	20	202296	
2	28.4	45	80	90	45	25	17	307339	
4	45	57	100	110	63.5	32	28	309303	
4H	45.4	52	100	110	63.5	32	28	205804	
4H	51	45	80	113.5	39	33	28	204335	
3	30	45	80	90	50	30	16	308756	
3	37	47.5	80	90	50	30	16	308806	
3H	37	45	80	90	50	30	16	307427	
3H	37	45	80	75	50	30	16	306665	
2H	28.4	45	100	80	42.5	22	16	309559	
2H	28.4	45	100	80	42.5	22	16	309560	
2	28	45	120	90	42.5	22	-	200750	
3	37	51	120	90	50	22	-	200752	
3	37	45	180	100	50	30	73.3	205512	
3H	37	50	180	100	50	30	73.3	206245	

*Note: Other Weld on Ball Ends Variations available